

FS100 ZENESIS™ V-NOTCH FLOOR SAW BLADE



PROFESSIONAL SERIES

ZENESIS™ V-NOTCH CONCRETE BLADE

The **FS100 Professional Series ZENESIS™ V-Notch Blade** represents the highest level of diamond blade performance for hard and reinforced concrete. The ZENESIS™ V-Notch pattern maximizes diamond exposure while improving cooling and debris removal, resulting in faster cutting, longer blade life, and consistent performance from the first cut to the last.

APPLICATION	EQUIPMENT
Concrete	Floor Saw

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT	12 mm (.472")	ARBOR	1" Drive Pin
MOUNTING PATTERN	LOU (12"-36") • LOU/ROG (42"-60")	CUTTING METHOD	Wet
BOND AVAILABILITY	Medium • Medium Hard • Hard	CONCENTRATION	30CON • 35COM

AVAILABLE SIZES

DIAMETER	AVAILABLE SEGMENT WIDTHS	MOUNTING
12"	.125", .155", .187", .250"	LOU
14"	.125", .165", .187", .250"	LOU
16"	.125", .165", .187", .250"	LOU
18"	.125", .165", .187", .250"	LOU
20"	.125", .165", .187", .250"	LOU
24"	.125", .165", .187", .220", .250"	LOU
26"	.165", .187", .220", .250"	LOU
28"	.155", .165", .187", .220", .250"	LOU
30"	.155", .165", .220", .250"	LOU
36"	.155", .165", .187", .220", .250"	LOU
42"	.187", .220", .250"	LOU/ROG
48"	.187", .220", .250"	LOU/ROG
54"	.187", .220", .250"	LOU/ROG
60"	.187", .220", .250"	LOU/ROG

Other diameters and segment thicknesses with 12 mm (.472") segment height are available upon request. Available in 30CON, and 35CON.

STANDARD ARBOR CONFIGURATION

The standard mounting pattern is automatically selected based on blade diameter. Alternate arbor configurations are available upon request.