

FS400 PROFESSIONAL SERIES FLOOR SAW BLADE



PROFESSIONAL SERIES

PROFESSIONAL SERIES ASPHALT BLADE

The **FS400 Professional Series Asphalt Blade** delivers fast cutting, long service life, and a low cost per cut when used on asphalt and other abrasive materials. Integrated undercut protection helps extend blade life by reducing steel core wear. Available in four bond specifications to match changing job-site conditions and offered in **35CON**, **40CON**, and **45CON** performance grades.

APPLICATION

Asphalt

EQUIPMENT

Floor Saw

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT 10 mm (.394")

ARBOR

1" Drive Pin

MOUNTING PATTERN LOU (12"-36") • LOU/ROG (42"-60")

CUTTING METHOD

Wet

BOND AVAILABILITY Very Soft • Soft • Medium Soft • Medium
Medium Hard • Hard

CONCENTRATION

35CON • 40COM • 45CON

AVAILABLE SIZES

DIAMETER	AVAILABLE SEGMENT WIDTHS	MOUNTING
12"	.125", .155", .187", .250"	LOU
14"	.125", .165", .187", .250"	LOU
16"	.125", .165", .187", .250"	LOU
18"	.125", .165", .187", .250"	LOU
20"	.125", .165", .187", .250"	LOU
24"	.125", .165", .187", .220", .250"	LOU
26"	.165", .187", .220", .250"	LOU
28"	.155", .165", .187", .220", .250"	LOU
30"	.155", .165", .220", .250"	LOU
36"	.155", .165", .187", .220", .250"	LOU
42"	.187", .220", .250"	LOU/ROG
48"	.187", .220", .250"	LOU/ROG
54"	.187", .220", .250"	LOU/ROG
60"	.187", .220", .250"	LOU/ROG

Other diameters and segment thicknesses with 10 mm (.394") segment height are available upon request. Available in 35CON, 40CON and 45CON.

STANDARD ARBOR CONFIGURATION

The standard mounting pattern is automatically selected based on blade diameter. Alternate arbor configurations are available upon request.