

GC101 STANDARD GRINDING CUP



CONSTRUCTION SERIES SURFACE PREPARATION

GRINDING CUP DOUBLE ROW

The **GC101 Double Row Diamond Grinding Cup Wheel** is designed for fast, efficient grinding of concrete, masonry, brick, block, and other abrasive construction materials. Featuring premium diamond segments, the GC101 provides aggressive material removal while delivering smooth, controlled performance for surface preparation, coating removal, edge grinding, and general concrete finishing. Engineered for professional contractors, the GC101 is suitable for both wet and dry applications and is available with **7/8"-5/8" B** or **5/8"-11 THD** connector options to fit most angle grinders.

APPLICATION

Concrete, Masonry

EQUIPMENT

Angle grinder

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT	5 mm (.196")	PERFORMANCE LEVEL	Standard
CONFIGURATION	Double segment	ARBOR	7/8"-5/8" B, 5/8"-11 THD
ASSEMBLY	Brazed	COOLANT	Dry / Wet

AVAILABLE SIZES

DIAMETER	SEGMENT HEIGHT	CONNECTOR
4"	5 mm (.196")	7/8"-5/8"-B, 5/8"-11 THD
4-1/2"	5 mm (.196")	7/8"-5/8"-B, 5/8"-11 THD
7"	5 mm (.196")	5/8"-11 THD