

## GC200 STANDARD GRINDING CUP



### CONSTRUCTION SERIES SURFACE PREPARATION

### GRINDING CUP SINGLE ROW TURBO

The **GC200 Single Row Turbo Grinding Cup** is engineered for fast, aggressive grinding of concrete, masonry, brick, block, and other construction materials. Its continuous turbo segment design delivers rapid material removal with improved cutting efficiency while helping to produce a smoother grinding finish than conventional segmented cup wheels. Designed for professional contractors, the GC200 is ideal for surface preparation, edge grinding, coating removal, and concrete leveling in both wet and dry applications.

#### APPLICATION

Concrete, Masonry

#### EQUIPMENT

Angel grinder

### TECHNICAL SPECIFICATIONS

|                |               |                   |                          |
|----------------|---------------|-------------------|--------------------------|
| SEGMENT HEIGHT | 5 mm (.196")  | PERFORMANCE LEVEL | Standard                 |
| CONFIGURATION  | Segment turbo | ARBOR             | 7/8"-5/8" B, 5/8"-11 THD |
| ASSEMBLY       | Brazed        | COOLANT           | Dry / Wet                |

### AVAILABLE SIZES

| DIAMETER | SEGMENT HEIGHT | CONNECTOR                |
|----------|----------------|--------------------------|
| 4"       | 5 mm (.196")   | 7/8"-5/8"-B, 5/8"-11 THD |
| 4-1/2"   | 5 mm (.196")   | 7/8"-5/8"-B, 5/8"-11 THD |
| 5"       | 5 mm (.196")   | 5/8"-11 THD              |
| 7"       | 5 mm (.196")   | 7/8"-5/8"-B, 5/8"-11 THD |