

GC301 STANDARD GRINDING CUP



CONSTRUCTION SERIES SURFACE PREPARATION

GRINDING CUP T-SEGMENT

The **GC301 T Segment Grinding Cup** is engineered for aggressive grinding and rapid material removal on concrete, masonry, stone, and other abrasive construction materials. Its heavy-duty **T segment design delivers increased grinding pressure and exceptional durability, making it ideal for demanding surface preparation**, leveling uneven concrete, removing coatings, and preparing floors for finishing. Manufactured with premium industrial diamonds, the GC301 provides fast, consistent performance in both wet and dry grinding applications.

APPLICATION

Concrete, Masonry, Stone

EQUIPMENT

Angel grinder

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT 5 mm (.196")

PERFORMANCE
LEVEL

Standard

CONFIGURATION T - segment

ARBOR

7/8"-5/8" B, 5/8"-11 THD

ASSEMBLY Brazed

COOLANT

Dry / Wet

AVAILABLE SIZES

DIAMETER	SEGMENT HEIGHT	CONNECTOR
4"	5 mm (.196")	5/8"-11 THD
4-1/2"	5 mm (.196")	5/8"-11 THD
5"	5 mm (.196")	5/8"-11 THD
7"	5 mm (.196")	7/8"-5/8"-B, 5/8"-11 THD