

GC302 STANDARD GRINDING CUP



CONSTRUCTION SERIES SURFACE PREPARATION

GRINDING CUP SINGLE ROW ARROW

The **GC302 Arrow Segment Grinding Cup** is engineered for aggressive surface preparation and rapid stock removal on concrete, masonry, natural stone, and other abrasive construction materials. Its specialized arrow segment design penetrates coatings and surface contaminants quickly while maintaining excellent grinding control and debris removal. Built for professional contractors, the GC302 is ideal for preparing concrete floors, removing coatings, leveling uneven surfaces, and cleaning edges in both wet and dry applications.

APPLICATION

Concrete, Masonry, Stone

EQUIPMENT

Angel grinder

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT	7 mm (.275")	PERFORMANCE LEVEL	Standard
CONFIGURATION	Arrow segment	ARBOR	7/8"-5/8" B, 5/8"-11 THD
ASSEMBLY	Brazed	COOLANT	Dry / Wet

AVAILABLE SIZES

DIAMETER	SEGMENT HEIGHT	CONNECTOR
5"	7 mm (.275")	5/8"-11 THD
7"	7 mm (.275")	7/8"-5/8"-B, 5/8"-11 THD