

GC400 PREMIUM GRINDING CUP



CONSTRUCTION SERIES SURFACE PREPARATION

GRINDING CUP S-SEGMENT

The **GC400 S-Cup Diamond Grinding Cup** is engineered for smooth surface finishing, edge grinding, and controlled material removal on concrete and masonry surfaces. Its precision S-Cup segment design provides excellent surface coverage while minimizing swirl marks, making it ideal for the early stages of polishing and surface preparation. **Available in multiple grit options**, the GC400 allows contractors to choose the finish best suited for each application while maintaining long service life and consistent grinding performance.

APPLICATION

Concrete

EQUIPMENT

Angel grinder

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT	4.5 mm (.177")	PERFORMANCE LEVEL	Premium
CONFIGURATION	S-segment	ARBOR	5/8"-11 THD
ASSEMBLY	Brazed	COOLANT	Dry / Wet

AVAILABLE SIZES

DIAMETER	SEGMENT HEIGHT	GRIT	CONNECTOR
5"	4.5 mm (.177")	16/18	5/8"-11 THD
5"	4.5 mm (.177")	30/40	5/8"-11 THD
5"	4.5 mm (.177")	60/80	5/8"-11 THD
5"	4.5 mm (.177")	120/140	5/8"-11 THD
7"	4.5 mm (.177")	16/18	5/8"-11 THD
7"	4.5 mm (.177")	30/40	5/8"-11 THD
7"	4.5 mm (.177")	60/80	5/8"-11 THD
7"	4.5 mm (.177")	120/140	5/8"-11 THD