

GP400 STANDARD BLADES



CONSTRUCTION SERIES BLADE

GENERAL PURPOSE BLADES

The **GP400 Series** is a **standard-performance keyhole slot diamond blade** engineered for dependable cutting of reinforced concrete, cured concrete, brick, block, and other common masonry materials. Its precision keyhole slot design improves cooling, reduces cutting resistance, and promotes efficient debris removal for smooth, consistent cutting performance. **GP400** delivers reliable cutting performance and excellent value for everyday professional applications.

APPLICATION

Reinforced concrete, Brick, Block, Cured concrete

EQUIPMENT

Masonry saw, High speed saw, Low-horsepower Walk-Behind saws

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT	10 mm (.394")	PERFORMANCE LEVEL	Standard
CONFIGURATION	Segmented	ARBOR	1" - 20mm DP, 1" - DP
ASSEMBLY	Laser welded	COOLANT	Dry / Wet

AVAILABLE SIZES

DIAMETER	AVAILABLE SEGMENT WIDTHS	Arbor
12"	.125"	1" - 20 mm DP
14"	.125"	1" - 20 mm DP
16"	.125", .140"	1" - 20 mm DP
18"	.125"	1" - DP
20"	.125", .140"	1" - DP
24"	.140"	1" - DP