

GP600 STANDARD BLADES



CONSTRUCTION SERIES BLADE

GENERAL PURPOSE TURBO SEGMENTED BLADES

The **GP600 Series** is a standard-performance turbo segmented diamond blade engineered for fast, efficient cutting of reinforced concrete, cured concrete, brick, block, and other common masonry materials. Its precision turbo segmented rim provides smoother cutting, improved cooling, and faster debris removal while reducing cutting resistance for extended blade life. **GP600** delivers dependable cutting performance, durability, and excellent value for everyday professional applications.

APPLICATION

Reinforced concrete, Brick, Block, Cured concrete

EQUIPMENT

Masonry saw, High speed saw, Low-horsepower Walk-Behind saws

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT	12 mm (.4724")	PERFORMANCE LEVEL	Standard
CONFIGURATION	Turbo segmented	ARBOR	1" - 20mm DP, 1" - DP
ASSEMBLY	Laser welded	COOLANT	Dry / Wet

AVAILABLE SIZES

DIAMETER	AVAILABLE SEGMENT WIDTHS	Arbor
12"	.125"	1" - 20 mm DP
14"	.125"	1" - 20 mm DP
16"	.125"	1" - 20 mm DP
18"	.125"	1" - DP
20"	.140"	1" - DP