

WS100 ZENESIS™ V-NOTCH WALL SAW BLADE



PROFESSIONAL SERIES

ZENESIS™ WALL SAW BLADE

The **WS100 Professional Series ZENESIS™ V-Notch Wall Saw Blade** represents the highest level of wall sawing performance for hard and reinforced concrete. Advanced ZENESIS™ patterned V-Notch segments provide superior cooling, faster cutting speeds, and extended blade life while maintaining exceptional cutting performance throughout the life of the blade. Available in four bond specifications (Medium Soft, Medium, Medium Hard, and Hard) to optimize performance for varying concrete conditions. Manufactured in **35CON** performance grade for maximum productivity in professional wall sawing applications.

APPLICATION	EQUIPMENT
Concrete	Hydraulic Wall Saw

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT	12 mm (.472")	ARBOR	1" Drive Pin or 1-3/8"
MOUNTING PATTERN	Longyear, GDM	CUTTING METHOD	Wet
BOND AVAILABILITY	Medium Soft · Medium · Medium Hard · Hard	CONCENTRATION	35CON

AVAILABLE SIZES

DIAMETER	AVAILABLE SEGMENT WIDTHS	MOUNTING
20"	.125", .187"	LYBHP / GDMBHP
24"	.125", .187", .210", .250"	LYBHP / GDMBHP
26"	.155", .165", .187"	LYBHP / GDMBHP
30"	.155", .187", .210", .250"	LYBHP / GDMBHP
36"	.187", .250"	LYBHP / GDMBHP
42"	.210", .250"	LYBHP / GDMBHP
48"	.187", .210", .250"	LYBHP / GDMBHP
54"	.187", .210"	LYBHP / GDMBHP
60"	.210", .250"	LYBHP / GDMBHP

Other diameters and segment thicknesses with 12 mm (.472") segment height are available upon request. Available in 35CON.

STANDARD ARBOR CONFIGURATION

The standard mounting pattern is automatically selected based on blade diameter. Alternate arbor configurations are available upon request.