

WS200 ZENESIS™ SPLIT SEGMENT WALL SAW BLADE



PROFESSIONAL SERIES

ZENESIS™ WALL SAW BLADE

The **WS200 Professional Series ZENESIS™ Split Segment Wall Saw Blade** represents advanced wall sawing technology for professional contractors cutting hard and heavily reinforced concrete. Precision-engineered ZENESIS™ Split Segments maximize cutting efficiency by improving cooling, reducing cutting resistance, and maintaining continuous diamond exposure for exceptional cutting speed and long blade life. Available in four bond specifications (Medium Soft, Medium, Medium Hard, and Hard) to optimize performance for varying concrete conditions. Manufactured in **20CON** performance grade to deliver maximum productivity in commercial and industrial wall sawing applications..

APPLICATION	EQUIPMENT
Concrete	Hydraulic Wall Saw

TECHNICAL SPECIFICATIONS

SEGMENT HEIGHT	10 mm (.394")	ARBOR	1" Drive Pin or 1-3/8"
MOUNTING PATTERN	Longyear, GDM	CUTTING METHOD	Wet
BOND AVAILABILITY	Medium Soft · Medium · Medium Hard · Hard	CONCENTRATION	20CON

AVAILABLE SIZES

DIAMETER	AVAILABLE SEGMENT WIDTHS	MOUNTING
20"	.125", .187"	LYBHP / GDMBHP
24"	.125", .187", .210", .250"	LYBHP / GDMBHP
26"	.155", .165", .187"	LYBHP / GDMBHP
30"	.155", .187", .210", .250"	LYBHP / GDMBHP
36"	.187", .250"	LYBHP / GDMBHP
42"	.210", .250"	LYBHP / GDMBHP
48"	.187", .210", .250"	LYBHP / GDMBHP
54"	.187", .210"	LYBHP / GDMBHP
60"	.210", .250"	LYBHP / GDMBHP

Other diameters and segment thicknesses with 10 mm (.394") segment height are available upon request. Available in 20CON.

STANDARD ARBOR CONFIGURATION

The standard mounting pattern is automatically selected based on blade diameter. Alternate arbor configurations are available upon request.